

**AMENDMENTS TO THE CLAIMS**

A listing of all claims and their current status in accordance with 37 C.F.R. § 1.121(c) is provided below.

1. (previously presented) A method for transmitting video graphics data, comprising:
  - dividing a screen into a number of blocks, the blocks having contents;
  - periodically reading the contents of each one of the blocks over a number of passes, wherein each pass reads a different fraction of all the blocks;
  - computing a unique value for a first block based on the contents;
  - comparing the unique value for the first block to a previously computed unique value corresponding to the first block; and
  - transmitting the contents of the first block if the unique value for the first block is different from the previously computed unique value corresponding to the first block.
2. (original) The method of claim 1, further comprising:
  - storing the unique value for the first block in a table if the unique values are different;
  - and
  - comparing the unique value of the first block to a unique value corresponding to a preceding block,
  - wherein the transmitting step transmits the preceding block and a repeat command if the unique value of the first block is equal to the unique value corresponding to the preceding block.

3. (original) The method of claim 1, further comprising:

storing the unique value of the first block in a table if the unique values are different;

comparing the unique value of the first block to a unique value corresponding to a preceding block; and

compressing the contents of the first block if the unique values are not equal,

wherein the transmitting step transmits the preceding block and a compressed first block if the unique value of the first block is not equal to the unique value corresponding to the preceding block.

4. (original) The method of claim 3, wherein the compressing step includes compressing a number of similar bytes using a run length encoding technique.

5. (original) The method of claim 1, further comprising:

periodically reading configuration information of a video graphics controller;

determining if the configuration information has changed; and

transmitting configuration changes if the configuration information has changed.

6. (original) The method of claim 5,

wherein the screen is divided into a number of blocks, including rows and columns, based on the screen resolution, and

wherein the configuration information is read after a row of blocks is completed.

7. (previously presented) The method of claim 1, further comprising:  
periodically reading configuration information of a pointing device;  
determining if the configuration information has changed; and  
transmitting configuration changes if the configuration information has changed.
8. (original) The method of claim 7,  
wherein the screen is divided into a number of blocks, including rows and columns,  
based on the screen resolution, and  
wherein the configuration information is read after a row of blocks is completed.
9. (cancelled)
10. (previously presented) The method of claim 1, wherein surrounding blocks are  
marked for accelerated processing if during one of the passes the unique value for a given  
block is different from a previously computed unique value corresponding to the given block.
11. (original) The method of claim 10, wherein each pass reads a different  
fraction of all the blocks and any blocks marked for accelerated processing.
12. (original) The method of claim 1, wherein the blocks contain color values, the  
method further comprising:  
condensing the color values into 6-bit red-green-blue color values before computing  
the unique values.

13. (previously presented) A method of transmitting video graphics data, comprising:

- dividing a screen into a number of blocks;
- reading a first block and at least one subsequent block wherein all the blocks are read over a number of passes and wherein each pass reads a different fraction of all the blocks;
- comparing the first block to a subsequent block;
- developing a repeat command based on how many subsequent blocks equal the first block; and
- transmitting the first block and the repeat command.

14. (original) The method of claim 13, comprising:

- periodically reading configuration information of a video graphics controller;
- determining if the configuration information has changed; and
- transmitting configuration changes if the configuration information has changed.

15. (original) The method of claim 14,

- wherein the screen is divided into a number of blocks, including rows and columns, based on the screen resolution, and
- wherein the configuration information is read after a row of blocks is completed.

16. (original) The method of claim 13, comprising:

- periodically reading configuration information of a pointing device;

determining if the configuration information has changed; and

transmitting configuration changes if the configuration information has changed.

17. (original) The method of claim 16,  
wherein the screen is divided into a number of blocks, including rows and columns,  
based on the screen resolution, and wherein the configuration information is read after a row  
of blocks is completed.

18. (cancelled)

19. (previously presented) The method of claim 13, wherein surrounding blocks  
are marked for accelerated processing if during one of the passes the unique value for a given  
block is different from a previously computed unique value corresponding to the given block.

20. (original) The method of claim 19, wherein each pass reads a different  
fraction of all the blocks and any blocks marked for accelerated processing.

21. (original) The method of claim 12, wherein the blocks contain color values,  
the method further comprising:

condensing the color values into 6-bit red-green-blue color values, before computing  
the unique values.

22. (previously presented) A method of transmitting video graphics data,  
comprising;

dividing a screen into a number of blocks;  
reading a first block of the screen;  
compressing the first block;  
reading a second block of the screen, wherein all the blocks are read over a number of  
passes and each pass reads a different fraction of all the blocks;  
comparing the first block to the second block;  
compressing the second block with the first block if the first and second blocks are not  
equal; and  
transmitting the compressed blocks.

23. (original) The method of claim 22, wherein the compressing step includes  
compressing a number of similar bytes using a run length encoding technique.

24. (previously presented) The method of claim 22,  
wherein surrounding blocks are marked for accelerated processing if during one of the  
passes the unique value for a given block is different from a previously computed unique  
value corresponding to the given block, and  
wherein the reading step includes reading a different fraction of all the blocks and  
any blocks marked for accelerated processing.

25. (previously presented) A computer system for communicating with a remote  
console, comprising:  
a video graphics controller having a frame buffer;  
a communication device; and

a processor coupled to the video graphics controller and the communications device,  
the processor configured to:

divide the frame buffer into a number of blocks;

periodically read the frame buffer and determine whether any of the blocks  
have changed since a previous reading, wherein the processor reads all of the blocks  
over a number of passes and wherein each pass reads a different fraction of all the  
blocks; and

transmit changed blocks to the remote console via the communications device.

26. (original) The computer system of claim 23, wherein a hash code is calculated  
and stored for each block when the block is first read, and wherein subsequent changes are  
determined for a given block by calculating a new hash code and comparing the new hash  
code to the stored hash code.

27. (original) The computer system of claim 26, wherein if subsequently  
positioned changed blocks have hash codes equal to a previously positioned block, the  
processor is configured to develop a repeat command to indicate how many times the  
previously positioned block is repeated prior to transmission.

28. (original) The computer system of claim 26, wherein if subsequently  
positioned changed blocks have hash codes unequal to a previously positioned block, the  
processor is configured to compress the subsequently positioned changed block prior to  
transmission.

29. (original) The computer system of claim 28, wherein the processor is configured to compress similar bytes within a block using a run length encoding technique.

30. (original) The computer system of claim 25, wherein the processor is further configured to:

periodically read configuration information of the video graphics controller;  
determine if the configuration information has changed; and  
transmit configuration changes if the configuration information has changed.

31. (original) The computer system of claim 30,  
wherein the screen is divided into a number of blocks, including rows and columns,  
based on the screen resolution, and  
wherein the processor reads the configuration information after a row of blocks is completed.

32. (original) The computer system of claim 25, wherein the processor is further configured to:

periodically read configuration information of a pointing device;  
determine if the configuration information has changed; and  
transmit configuration changes if the configuration information has changed.

33. (original) The computer system of claim 32,  
wherein the screen is divided into a number of blocks, including rows and columns,  
based on the screen resolution, and



wherein the processor reads the configuration information after a row of blocks is completed.

34. (cancelled)

35. (previously presented) The computer system of claim 25, wherein the processor marks surrounding blocks for accelerated processing if during one of the passes the unique value for a given block is different from a previously computed unique value corresponding to the given block.

36. (original) The computer system of claim 35, wherein each pass reads a different fraction of all the blocks and any blocks marked for accelerated processing.

37. (previously presented) A computer system for communicating with a remote console, comprising:

a video graphics controller having a frame buffer;

a monitor connectable to the video graphics controller;

a communication device; and

a processor coupled to the video graphics controller and the communications device,

the processor configured to:

divide the frame buffer into a number of blocks;

periodically read the frame buffer and determine whether any of the blocks

have changed since a previous reading, wherein each of the blocks are read over a

number of passes and wherein each pass reads a different fraction of all the blocks;  
and  
transmit changed blocks to the remote console via the communications device.

38. (previously presented) An apparatus for updating video graphics data for a remote console, comprising:  
means for dividing a frame buffer into a series of blocks;  
means for reading one of the blocks, wherein each of the blocks are read over a number of passes and wherein each pass reads a different fraction of all the blocks;  
means for computing a hash code for the block;  
means for comparing the hash code to a previously computed hash code for the block ;  
and  
means for transmitting the block if the hash codes are not equal.